




DB - 100

The **BEL**'s Drop Bolt locks are renowned for its excellent reliability and the remarkable features.

The series complies to CE and manufactured under the highest quality control to achieve the commitment to customer who always satisfied with




SPECIFICATIONS:

- **Voltage Input :** 12 VDC
- **Current Draw :** 100mA (Standby) ; 1000mA (Start)
- **Locking Force :** Up to 800KG
- **Sensor Monitor Rating :** 0.5Amp,30VAC/VDC max
- **Gap Sensing Distance :** 8mm
- **Material :** Solid S/Steel Ø16mm Bolt
- **Operating Temperature :** 0~55° C (14~131° F)
- **Operating Humidity :** 0~90% (non condensing)
- **Weight (Magnet) :** 0.7 kg
- **Dimensions :** Face Plate - (L)205x(W)35x(H)40 mm
Strike - (L)90x(W)25x(T)2 mm



FEATURES:

- Failed Safe Operation (energized to lock)
- Low Surface Temperature
- Low Power Consumption
- Door Status Output NC & COM
- Reliable Locking Mechanism (MTBF Up to 500,000 Cycles)
- Auto Re-lock Timer 0,3,6,9 sec.
- Durable and Silent Operation
- Continuous Line Finish Aluminum Surface
- Reverse Current Protection PCB
- Full Range of Optional Brackets
- Standard Packing - 30 units



Auto Re-Locking
Timer Settings

WIRING INSTRUCTION:-

- RED** - Positive (+)
BLACK - Negative (-)
WHITE - NC & COM

Security . Quality . Reliability