

# AIRKEY Wireless EM Lock

Upto 40 Wireless Remotes can be Enrolled

Miroprocessor based , Auto Voltage Selection ,  
Relock Delay Timer , Internal/ External buzzer ,  
Security Conditioned Output of Door sensor and Bond Sensor  
Combine , Exit Button Trigger and Door Sensor Input


## Sekurit AIRKEY is World's First Wireless Em Lock with Loads of Advance Features

No Need of External RF Receivers and other additional Devices . All in One inbuilt Design

Simple and Easy Installation . Works with RF remote and also Standard Access Control System



Unique RGB Led for  
Showing Various Status of  
Lock in different Colours



- . **Holding Force** : Up to 600 lbs
- . **Weight ( Magnet )** : 1.1 kg (±1%)
- . **Dimensions** : Magnet - (L)250x(W)42x(T)25 mm  
Armature - (L)180x(W)38x(T)11 mm
- . **Anti Residual Magnetism Kick Off Button**
- . **Current Draw** : 12V /550 mA ; 24V / 320 mA (±5%)

### Sek-Airkey-AV-600 -led-DMS-Buzzer- Super Long Range

Wireless Range : upto 200 metre in Open Space

RF Remote Functions :

- \* Timer Unlock Mode
- \* Passage Mode ( Permanent Open )
- \* Alarm on-Off



### Technical Specifications :

( Miroprocessor based , Auto Voltage Selection )

- 1) Standby Current without lock:
  - 70mA to 80mA @12VDC & 60mA to 70mA @24VDC
- 2) Internal / External Buzzer Output : 80mA to 100mA @12VDC
- 3) Door Sensor Input
- 4) Exit Button Trigger Input
- 5) **Security Conditioned Combine Sensor Output** ( Combined Output of Door Sensor and hall sensor to give True Output of Lock open- close & Door Open-close ( Jumper Settings to Enable / Disable / Select Individual )
- 6) Lock Output : 0.8A to 0.85A @12/24VDC
- 7) Dual voltage 12/24VDC auto selection(Pluto buzzer)
- 8) MOV prevents voltage spike and surge current
- 9) No residual magnetism
- 10) Built-in Hall sensor and door status sensor input
- 11) Built in jumper for selection between Hall sensor and door status sensor input
- 12) Bi-color status Red/Green LED indicator
- 13) LED output voltage 20mA 9-10 VDC
- 14) Relock time delay: 0 to 120 Sec.
- 15) Isolated status output NO NC COM Rating : 2A/120VAC 1A/24VDC

### Sek-Airkey-AV-600 -led-DMS-Buzz ( Normal Range )

Wireless Range : upto 60 metre in Open Space

RF Remote Functions :

- \* Timer Unlock Mode

